

Technical Specifications

CAS 50Hz, R410A

Indoor Unit		CAS024V5			
Outdoor Unit "COOLING ONLY"		G+ OTV 018	G+OTV 020	G+OTV 025	
Outdoor Unit "HEAT PUMP"		G+ OHV 018	G+OHV 020	G+OHV 025	
Energy Class (Cooling)		C	C	C	
Nominal Cooling Capacity	kW-Btu/hr	5.22 17800	5.63 19200	6.70 22800	
Nominal Heating Capacity	kW-Btu/hr	4.66 15900	5.33 18200	6.24 21300	
Cooling Power Consumption	W	1823	1966	2387	
Heating Power Consumption	W	1700	2043	2587	
EER. Cooling*	W/W	2.86	2.86	2.81	
COP. Heating*	W/W	2.74	2.61	2.41	
Power Supply	V/Ph/Hz	220 - 240 / 1 / 50			
Air Flow Rate(at high speed & dry coil)	m3/hr	710			
	CFM	420			
Dimensions - Front Panel (WxHxD)	Net mm	665x665x30			
Dimensions - Indoor Unit (WxHxD)	Net mm	574x574x268			
Dimensions - Outdoor Unit (WxHxD)	Net mm	945x649x356		945x845x356	
Net Weight-Indoor unit	Kg	23.5			
Net Weight-Outdoor unit	Kg	53	58	77	
Refrigerant Type		R410A			

At Nominal rating Condition (Eurovent Condition):

Cooling: 35°C outdoor DBT / 27°C indoor DBT & 19°C indoor WBT.

Heating : 7°C outdoor DBT & 80% relative humidity / 20°C indoor DBT.

* Test volt: 230 at 50 Hz

Specifications are subject to change without prior notice